
	EMF/NIR Report		Radiofrequency electromagnetic fields measurement survey	
	Version	Reference #	Issue Date	Issued by
	1.0	2021/06	21 June 2021	J Vila

1. Measurement survey characteristics

Measurement date:	14 th May 2021
Measurement time:	11:30 am – 13:00 pm
Measurement point & location:	Fitzwilliam Square, Wicklow, Co Wicklow
GPS coordinates:	52°58'50.5" N; 6°2'35.2" W
Survey staff:	Javier Vila, Michael Murray
Purpose of the survey:	<p>1) To carry out measurements of radiofrequency (RF) electromagnetic fields (EMF) at a location within Wicklow town with high daytime population.</p> <p>2) To determine typical RF EMF levels and compare them with relevant exposure limits recommended by the International Commission on Non-Ionizing Radiation Protection (ICNIRP).</p> <p>This survey is part of the EPA’s national EMF monitoring programme (see reference EPA 2020 for more details).</p>
Measurement point description:	Outdoor public space typically busy due to available amenities in the area.

2. Summary of survey results


Measurement result:	The average total RF level measured was 0.32 V/m. This value is below ICNIRP’s recommended exposure limits of 28 V/m for radiofrequencies < 400 MHz and 61 V/m for radiofrequencies > 2 GHz.
Measured RF sources/signals:	2G (GSM), 3G (UMTS), 4G (LTE), Wi-Fi, PMR, FM Radio
Number of nearby telecommunication sites:	3 nearby sites (see map on page 4 for details). This information was obtained from the ComReg’s website https://siteviewer.comreg.ie/

 Environmental Protection Agency An tSionannacht um Daoimhíní Ceimiceach	EMF/NIR Report	Radiofrequency electromagnetic fields measurement survey		
	Version	Reference #	Issue Date	Issued by
	1.0	2021/06	21 June 2021	J Vila

3. Measurement methodology and results

Broadband and frequency-selective EMF measurements were performed at a location in Wicklow town centre (Fitzwilliam Square) known to have a high daytime population. The charts and tables below contain the summary results for total RF electric fields (Table 1 & Figure 1) and frequency-specific RF electric fields (Table 2 & Figure 2) for the selected location and time of the day using various configurations, including the use of a 5G-enabled mobile phone handset in the proximity of the measurement point while streaming video to identify any potential nearby 5G signals.

Figure 1. Total RF electric field levels at measurement point using two broadband probes.



Note: This graph represents total average (rms) RF electric fields measured for 6 minutes (360 seconds) using two different RF probes (100 kHz - 6 GHz and 100 MHz - 90 GHz) as described on the graph legend. Total RF fields include exposures from all RF sources (signals), depending on the probe used. *Strictest ICNIRP reference level for the entire RF range.

Table 1. Summary of total RF fields at measurement point using two broadband probes.

Probe Frequency Range	Average electric field (V/m)	Average power density (W/m ²)	Maximum electric field (V/m)	Maximum power density (W/m ²)	ICNIRP reference level (V/m)	ICNIRP reference level (W/m ²)
100 kHz - 6 GHz	0.32	0.0003	1.61	0.007	28*	2*
100 MHz - 90 GHz	0.25	0.0002	1.39	0.005	28*	2*

Note: RF electric field data obtained with Narda NBM-550 meter with EF0691 and EF9091 probes. *Strictest ICNIRP reference levels for the entire RF frequency range. These data have a maximum overall uncertainty around ±41% (±3 dB).



	EMF/NIR Report		Radiofrequency electromagnetic fields measurement survey	
	Version	Reference #	Issue Date	Issued by
	1.0	2021/06	21 June 2021	J Vila

Figure 2. Frequency-specific radiofrequency electric field level by telecommunication signal




Note: RF electric field data above the noise threshold for 6-min average (rms) obtained with SRM-3006 meter/spectrum analyser using 3501/03 and 3502/01 probes. *ICNIRP reference level for each corresponding frequency range. PMR: Professional mobile radio; 2G: GSM; 3G: UMTS; 4G: LTE; DL: Downlink; UL: Uplink.

Table 2. Measured average and maximum frequency-specific field level by RF source/signal.

RF Source / Telecommunication Signal	Frequency Range (MHz)	Maximum Electric Field/ Power Density		Average Electric Field/ Power Density		ICNIRP Reference Level ^b	
		(V/m)	(W/m ²)	(V/m)	(W/m ²)	(V/m)	(W/m ²)
PMR	680-748	0.14	0.00005	0.02	0.000001	36.7	3.6
FM Radio	875-1080	0.11	0.000032	0.1	0.000027	43.0	4.9
4G (800, DL)	791-821	0.23	0.00014	0.16	0.000068	39	4.0
2G-3G (900, DL)	925-960	0.13	0.00004	0.1	0.000027	42.2	4.7
2G-4G (1800, UL)	1710-1785	0.02	0.000001	0.01	0.0000003	57.5	8.7
2G-4G (1800, DL)	1805-1880	0.11	0.00003	0.08	0.000017	59.0	9.2
3G-4G (2.1, UL)	1920-1980	0.18	0.00008	0.02	0.000001	60.7	9.8
3G-4G (2.1, DL)	2110-2170	0.09	0.00002	0.05	0.000007	61	10
Wi-Fi 2.4GHz	2400-2483.5	0.1	0.00002	0.01	0.0000003	61	10


Note: RF electric field data above the equipment noise threshold for 6-min average (rms) obtained with SRM-3006 meter using 3501/03 and 3502/01 probes. These data have a maximum overall uncertainty around $\pm 41\%$ (± 3 dB). ^bICNIRP reference level for each corresponding frequency range. PMR: Professional mobile radio; 2G: GSM; 3G: UMTS; 4G: LTE; DL: Downlink; UL: Uplink.

 Environmental Protection Agency An Ghníomhaireacht um Daoimhiní Cúlchruaidh	EMF/NIR Report	Radiofrequency electromagnetic fields measurement survey		
	Version	Reference #	Issue Date	Issued by
	1.0	2021/06	21 June 2021	J Vila


5. Conclusion – Total & Frequency-Specific RF field levels


Measured (average and maximum) total RF electric field levels (Figure 1 & Table 1) were below the strictest ICNIRP recommended exposure limit for the entire RF frequency range (i.e. 28 V/m). The average total RF level was 0.32 V/m. Measured (average and maximum) frequency-specific RF electric field levels for all detected signals (Figure 2 & Table 2) were low (< 1 V/m). All the signals measured were below the corresponding ICNIRP recommended exposure limits of 28 V/m for radiofrequencies < 400 MHz and 61 V/m for radiofrequencies > 2 GHz. The highest RF electric field level at the point of measurement (0.23 V/m) is likely to correspond to the emission (downlink) from nearby 4G/LTE antennas. No 5G signals were detected at the point of measurement.

6. Map of measurement point and nearby telecommunication sites



7. Photo of measurement point nearby (line-of-sight) telecommunication sites



 Environmental Protection Agency An Ghníomhaireacht um Daoimhiní Cúlraíochtaí	EMF/NIR Report		Radiofrequency electromagnetic fields measurement survey	
	Version	Reference #	Issue Date	Issued by
	1.0	2021/06	21 June 2021	J Vila

Appendix

A1. Equipment characteristics and calibration

The following EMF measurement equipment were used:

- Narda SRM-3006 frequency-selective meter and spectrum analyser.
- Narda NBM-550 broadband survey meter.
- Narda probes covering a frequency range between 100 kHz and 90 GHz.
- All equipment was calibrated in July 2019.

A2. References

- EPA 2020. EMF Monitoring Programme 2021-2023.
<https://www.epa.ie/radiation/emf/emfmonitoringprogramme/>
- ECC RECOMMENDATION (02)04. Measuring Non-Ionising Electromagnetic Radiation (9 kHz – 300 GHz) (Bratislava 2003, Helsinki 2007)
www.erodocdb.dk/Docs/doc98/official/pdf/REC0204.PDF
- I.S. EN 62232-2017. Determination of RF field strength, power density and SAR in the vicinity of radiocommunication base stations for the purpose of evaluating human exposure. NSAI Standards; CENELEC 2017 <https://shop.standards.ie/en-ie/>
- European Commission (EC) 1999/519/EC: Council Recommendation of 12 July 1999 on the limitation of exposure of the general public to electromagnetic fields (0 Hz to 300 GHz) <https://op.europa.eu/en/publication-detail/-/publication/9509b04f-1df0-4221-bfa2-c7af77975556/language-en>
- International Commission on Non-Ionizing Radiation Protection (ICNIRP). Guidelines for Limiting Exposure to Electromagnetic Fields (100 kHz to 300 GHz). Health Physics 2020 May;118(5): 483-524
<https://pubmed.ncbi.nlm.nih.gov/32167495/>